This item was submitted to [Loughborough's Research Repository](#) by the author.
Items in Figshare are protected by copyright, with all rights reserved, unless otherwise indicated.

Development and testing of a micro wind tunnel for on-site wind erosion simulations

PLEASE CITE THE PUBLISHED VERSION

<http://dx.doi.org/10.1007/s10652-016-9478-8>

PUBLISHER

© Springer Science+Business Media Dordrecht

VERSION

AM (Accepted Manuscript)

PUBLISHER STATEMENT

This work is made available according to the conditions of the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International (CC BY-NC-ND 4.0) licence. Full details of this licence are available at:
<https://creativecommons.org/licenses/by-nc-nd/4.0/>

LICENCE

CC BY-NC-ND 4.0

REPOSITORY RECORD

Strong, Craig L., John Leys, Mike R. Raupach, Joanna Bullard, Helene A. Aubault, Harry J. Butler, and Grant H. McTainsh. 2019. "Development and Testing of a Micro Wind Tunnel for On-site Wind Erosion Simulations". figshare. <https://hdl.handle.net/2134/22348>.

Keywords. *Erodibility, Field studies, Dust, Methodology, Land use, rangelands, mine storage facilities.*

1 Introduction

Wind erosion is widespread across natural and anthropogenic surfaces and occurs worldwide where wind speeds exceed the threshold velocity required to detach soil or sediment particles and transport them. The susceptibility of a surface to wind erosion can be measured in a variety of ways including field-based monitoring of wind regime and sediment transport [1-2], using laboratory or field-based wind tunnels [3-5], portable wind erosion facilities [6] and modelling [7-9]. Each approach has advantages and limitations [5] and this paper focuses on the use of a field wind tunnel.

Despite the increasing variety of techniques available for studying wind erosion, wind tunnels, which are one of the earliest approaches [10], are still very widely used. The usefulness and validity of wind tunnels depends on them adequately simulating the natural processes of wind and for this reason they have typically been constructed to be as large as possible to minimize scaling effects [11]. Whilst fixed location, stationary wind tunnels used for aeolian research can be very large, for example the Chinese Academy of Sciences has a 38 m lab based tunnel [12], their limitation is that they are generally only used with artificial soil surfaces. In contrast, portable wind tunnels typically have an open floor, and can be moved around in the field to simulate wind erosion of surfaces *in situ*. Van Pelt et al. [5] provide a useful review of portable wind tunnels used in wind erosion research and highlight that although these tunnels are 'portable' they are often large (e.g. cross-section up to 1 m² and length over 10 m) and require considerable logistical support for deployment. Large portable tunnels also have the disadvantage of requiring space around the tunnel for locating generators, trucks, trailers and ancillary equipment.

In many situations it is difficult and expensive to deploy such large wind tunnels in the field due to physical limitations of; site access (e.g. unmade roads), steepness of slopes (e.g. on mine spoils), and cost of labour required to rig and operate the tunnel. Also, on vegetated field sites aerodynamic 'noise' is introduced because of difficulties in achieving a good seal between the soil surface and the tunnel [13]. The working section beneath large tunnels can also homogenise the effects of spatial variations in soil surfaces, such as changes in sediment size and soil crust characteristics [14]. Some small portable wind tunnels have been developed and successfully used in the field. For example the wind tunnel constructed by Gillette [15] had a small cross section of 150 mm x 150 mm and length of 3 m and was used to determine threshold friction velocities on biological crusted soil surfaces [16-17]. An alternative approach is the Portable In Situ Wind EROsion Lab (PI-SWERL). The PI-SWERL differs from duct-type wind tunnels in that it uses rotating airflow within a 0.57 m diameter cylinder to generate shear stresses on the surface. Despite this fundamental difference, the results from the PI-SWERL compare well with those from conventional duct-type wind tunnels [18].

The present paper describes the development and testing of a new micro wind tunnel (MWT) designed for field simulation of wind erosion on small plots. The MWT is a duct-type design and is novel because it can be deployed by a single person on slopes ranging from 0-10 degrees. Three examples are provided to illustrate the application of the device measuring the erodibility of rangeland and claypan soils, and of stockpiles at an iron ore storage facility.

2 Materials and Methods

Numerous researchers have proposed practical and aerodynamic criteria to be met by the design of portable wind tunnels [19, 20]. These design criteria are summarised by Maurer et al. [13] as

- the tunnel must achieve wind speeds that reflect natural conditions;
- the tunnel should produce realistic aerodynamic flows within;
- the tunnel must be easy to transport, assemble and handle

and the criteria have been recently reviewed by Van Pelt et al. [5]. In addition, for wind erosion studies it is important that the full range of aeolian sediment transport processes (creep, saltation, suspension) can occur, and that saltating grains can be introduced at the upwind end of the working section to simulate the saltation impact process [20].

2.1 Design and Construction

The MWT has seven key components: a motor and tunnel wind velocity regulator, transition, working and exhaust sections, sediment trap, saltation injection tube and wind speed sensors (Figure 1). The motor is a 0.55 kW electric 240-volt induction motor that turns a 280 mm axial fan. The motor creates suction through the tunnel generating a velocity range of 5-18 m s⁻¹. Wind velocity is controlled via a calibrated baffle plate on the motor exhaust; complete blockage of the exhaust produces zero velocity whilst no blockage allows maximum velocity. Air is drawn into the tunnel through an opening 220 x 50 mm which contracts over 250 mm to a cross section 100 x 50 mm thus accelerating and stabilising the airflow. This stabilisation and organisation of airflow continues through the 1100 mm long transition section (aluminium box tube) downwind of which is a 1000 mm long working section. Within the working section the aluminium floor has been removed allowing direct contact between the wind and the soil surface. The top of the working section has a Perspex viewing window. Keyholes drilled in the top at distances of 100, 450 and 900 mm from the upwind end of the working section allow access for velocity measurement instruments (1 mm Dwyer pitot-static tubes) and are sealed with silicone plugs when not in use. Downwind of the working section is the 705 mm long exhaust section in which tunnel wind velocity is measured, wind transported sediment is sub-sampled via the sediment trap and the cross-section changes from rectangular to circular to

118 allow connection to the induction motor. A manually operated flow bypass valve within the
 119 exhaust section enables the operator to control when air is drawn through the tunnel. This
 120 avoids the ramp up / ramp down wind speeds associated with the motor being turned on/off
 121 being drawn across the tested surface. When the flow bypass value is lowered, air is
 122 sucked from the roof within the exhaust section, avoiding flow over the working section.
 123 Once the motor has reached maximum revolution, the flow bypass valve can be raised
 124 redirecting suction (flow) to the tunnel inlet, ensuring desired wind speed is passed over the
 125 working section. The total tunnel footprint including all sections is 3050 mm x 120 mm. The
 126 generator and tunnel motor are connected via 5 m lengths of ducting (76 mm diameter) and
 127 can be positioned away from the operating tunnel. All equipment is contained in four boxes
 128 and transported (including the generator) in a standard box trailer (1800 x 1200 mm).

129

130 **Fig. 1 Schematic diagram of the Micro Wind Tunnel (MWT) displaying the three sections (transition, working**
 131 **and exhaust) and velocity measurement options (pressure ports and pitot-static rake) present. The flow bypass**
 132 **valve enables air to be drawn through the tunnel from the suction induction motor attached at the rear. Sediment**
 133 **transported in the tunnel is subsampled at the sediment trap and collected on filter papers housed in the sediment**
 134 **filter box.**

135

136 Due to the importance of saltation-impact entrainment in wind erosion of soils [20] saltation
 137 material can be added to the wind flow using a saltation injection tube. The injection tube is

a 40 mm diameter acrylic tube, positioned at the upwind end of the transition section, which narrows to 2 mm diameter at the base. The injection tube can be opened or sealed using a tapered stainless-steel rod controlled using a solenoid that lifts the rod 10 mm vertically. The solenoid can be activated at the same time as the bypass valve in order to synchronise saltation injection with the start of tunnel flow. Transported sediment is collected via a vertical slot sampler 10 mm wide and 50 mm high. This is located on the centre line of the tunnel and is used to sub sample (10 %) of the sediment-laden tunnel airflow. Air from the sediment sampler is drawn vertically through a 38 mm hose to the sediment filter box which houses 125 mm-diameter glass-fibre filter papers with 0.1 μm pores.

For any one run, wind speed within the tunnel can be measured simultaneously at three different locations using pressure transducers connected to pitot-static tubes or roof mounted pressure ports or a combination of the two. The 1 mm dynamic port Dwyer pitot-static tubes can be positioned in a streamwise array at 100 mm, 450 mm and 900 mm from the upwind end of the working section along the centre line. Alternatively, at each of these locations, they can be arranged crosswise on the centre line and 25 mm from each wall (i.e. 3 equidistance measurements cross-flow). A pitot-static tube can also be located within the sediment trap at the downwind end of the tunnel. The pressure ports are fitted inside the tunnel, flush with the roofline, and located along the centre line at 300 mm intervals in the transition section and 200 mm intervals in the working section (nine in total). The most common field sampling configuration is one pressure transducer connected to a pitot tube at 900 mm upwind at the cross sectional mid-point, one pressure transducer connected to a pitot tube in the sediment sampler and the last pressure transducer connected to opposite end roofline pressure ports (i.e. pressure port numbers one and nine). Where more than three velocity measurements are required to characterise three dimensional flow structures, the tunnel can be run multiple times at a fixed reference velocity with the pressure transducers in different configurations. Data can be made dimensionless by relating all measurements to a fixed reference point. Temperature of the tunnel airflow and barometric air pressure are measured every second and averaged over 1 minute to enable the calculation of air density.

2.2 Airflow Measurements

A range of tests were undertaken to characterise: a) the range of tunnel wind velocities achieved within the tunnel, b) the uniformity of airflow and c) to develop an alternative technique of calculating u_* other than from logarithmic velocity profiles.

Tunnel wind velocity is controlled by raising or lowering the baffle plate on the induction motor exhaust (Figure 1). To determine the relationship between baffle position and tunnel velocity the MWT was run as it would be in the field (i.e. with filters in place) but over a smooth control surface (4 mm ABS plastic sheet, 'glassy' side up). Each baffle position was replicated 19 times and the MWT was run for one minute per replicate. Wind speed was measured using the pitot-static tubes and roof mounted pressure ports. Each baffle position created a different wind speed ranging from 5-18 m s^{-1} with excellent reproducibility (all standard errors lie within $\pm 0.002 \text{ m s}^{-1}$ of the mean value) (Figure 2).

Fig. 2 Airflow velocity (m s^{-1}) is determined by the position of the exhaust baffle. **A)** Velocity profiles measured with pitot-static tubes over a smooth test surface. Measurements made with a pitot rake at $x = 900$, $y = 50$, $z = 15$, 25 and 35 . SE included (19 reps/baffle position). **B)** Comparison of airflow velocities (m s^{-1}) measured using pitot-static tubes (squares) at $x = 900$, $y = 50$, $z = 25$ (SE included) and pressure port measurements at $x = 200$ and 900 , $y = 50$, $z = 50$ (SE included). All testing conducted on the same smooth surface. All standard errors lie within $\pm 0.002 \text{ m s}^{-1}$ of the mean values

Ideally a wind tunnel should produce uniform airflow across the tunnel and develop a logarithmic profile of wind velocity with height. To test these, with the baffle in position 2.5, wind speed was measured at 25 mm, 50 mm and 75 mm distance across the tunnel (y axis)

at 9 different heights (5, 10, 15, 20, 25, 30, 35, 40, 45 mm; z axis) and located at 100 mm, 450 mm and 900 mm from the upwind end of the working section (x axis). This approach provides a grid of 27 velocity measurements at each downwind location and shows how cross-flow uniformity varies with distance down the working section. If all the measurements had been taken simultaneously the instrumentation would have blocked the airflow in the tunnel and set up secondary airflow patterns, so, given the uniformity of wind speeds indicated in Figure 2, measurements were taken at 3 locations at a time for the same baffle position and combined to create the data grid. These tests were repeated over three artificial surfaces, one smooth (ABS plastic as above), one of medium roughness (40 grit sand paper), and one rough (10 mm diameter marbles protruding 2 mm above the test bed).

All surfaces within the tunnel are sources of drag, and the cross-sectional contour plots indicate that changes in floor roughness create the greatest changes in the flow symmetry (Figure 3). As floor roughness increases, flow lines compress near the floor surface. Figure 3 also indicates there is a slight surface imperfection in the top left hand corner where the Perspex working section ceiling is affixed. This has changed the flow symmetry slightly with slower flow along the left side. Despite this, the flow in the tunnel reflects what would be expected in a rectangular duct which is a fully developed flow. The length of the tunnel means this fully developed flow is also turbulent in nature and there is no logarithmic velocity profile as expected in larger wind tunnels.

Fig. 3 Contour plots of airflow velocity (0.2 m s^{-1} intervals) for smooth, medium and rough test surfaces showing the cross-sectional profile of the tunnel at 100, 450 and 900 mm from the upwind end of the working section. Airflow direction is away from the reader

216 As the MWT is a duct with a fully developed flow the shear stress and the friction velocity
 217 are calculated by measuring the pressure gradient not by the traditional approach of using
 218 logarithmic velocity profiles [5, 15, 19, 20]. Pressure drop along the length of a duct is well
 219 understood within fluid mechanics [21, 22]. The approach taken here is to partition the
 220 contribution that an open floor (one wall of the duct) has on the total duct pressure
 221 gradients in order to calculate the shear stress and the friction velocity on that surface. The
 222 following describes the approach taken.

223 Internal flow within a duct is constrained by bounding walls and the viscous effect which
 224 permeates the entire flow. Inviscid flow enters the duct and viscous boundary layers flow
 225 downstream retarding the axial flow $u(y,z)$ at the wall, thereby accelerating the centre of the
 226 flow to maintain the incompressible continuity requirement [21].

$$Q = \int_A u(y, z) dA = \text{constant}$$

227
228 (1)

229 Where Q is volume flow, $u(y,z)$ is flow velocity and A is cross sectional area. At a finite
 230 distance from the entrance the boundary layers merge and the inviscid core disappears.
 231 The duct flow then is entirely viscous and the axial velocity adjusts until it is fully developed.
 232 The distance (x) downstream that this occurs is referred to as the entrance length (L_e).
 233 Downstream of $x \geq L_e$ the velocity profile $u(y,z)$ is constant, wall shear is constant and
 234 pressure drops linearly with x for either laminar or turbulent flow. Dimensional analysis
 235 indicates the Reynolds number (Re_e) is the only parameter affecting entrance length L_e . Re_m
 236 is the Reynolds number for the MWT and calculated by

$$Re_m = \frac{\rho U}{\nu} D_h$$

237 (2)

$$= \omega D_h$$

238 (3)

239 where U is the average flow velocity, ρ is the density of air, ν is the viscosity of air, D_h is the
 240 hydraulic diameter, and ω is the scaled flow velocity. In a rectangular duct, the hydraulic
 241 diameter is determined as

$$D_h = \frac{2 \times \text{area}}{\text{width} + \text{height}}$$

242 (4)

243

244 The MWT has Reynolds numbers ranging from $26,500 < Re_m < 80,000$ (i.e. fully turbulent
 245 flow) [22]. In ducts with turbulent flows, the boundary layers grow faster and L_e is relatively
 246 short:

$$\frac{L_e}{D_h} \approx 4.4 Re_m^{\frac{1}{6}}$$

247 (5)

248 Therefore whilst the MWT does not support a log profile, the entrance length (L_e) effect is
 249 restricted within the transition section of the tunnel leaving the fully developed flow region to
 250 occur within the working section (Figure 1). This is important because it is in the working
 251 section that a developed velocity profile $u(y, z)$ needs to occur if changes in surface
 252 roughness are to be determined.

253 In larger wind tunnels the surface roughness is calculated from the wind profile. However,
 254 the micro wind tunnel does not support a log profile, thus an alternative technique for
 255 calculating u_* , the friction velocity, is required. The friction velocity (u_*) is frequently used to
 256 measure the wind speed required to initiate sediment movement.

257 The integral momentum method [23 in 24] is used here to calculate u_* . This paper shows
 258 that the friction velocity can be determined by measuring pressure gradients and using
 259 integral momentum balance. Theoretically, in a fully developed duct flow, the integral
 260 momentum balance is:

$$261 \quad \int_P \rho u_*^2 dP = -A \frac{dp}{dx} \quad (6)$$

262 where u_* is the friction velocity, ρ is air density, ρu_*^2 is the drag on the surface of the duct, P
 263 is the perimeter of the duct, dP is increment of the perimeter, A is the cross-sectional area
 264 of the duct and $\frac{dp}{dx}$ is the stream-wise pressure gradient. Therefore, in a rectangular duct of
 265 height Z and breadth Y :

$$266 \quad 2(Y + Z)u_{*a}^2 = -\frac{YZ}{\rho} \frac{dp}{dx} \quad (7)$$

267 where u_{*a} is an area-weighted average friction velocity for all surfaces around the tunnel
 268 circumference. The turbulence and secondary flow within the duct as documented by
 269 Schetz and Allen [22] act to equalise the shear stress across the perimeter of the duct.
 270 Thus, it is possible to partition the friction velocity to the various surfaces, hence the floor
 271 contributes a length Y to this average and the sides and roof together contribute a length
 272 $(2Z + Y)$. Consequently:

$$273 \quad 2(Y + Z)u_{*a}^2 = Yu_{*f}^2 + (2Z + Y)u_{*s}^2 \quad (8)$$

275 where u_{*f} is the friction velocity for the rough floor and u_{*s} is the friction velocity for the
 276 smooth sides and roof. Equating Equations 7 and 8 gives:

$$277 \quad Yu_{*f}^2 + (2Z + Y)u_{*s}^2 = -\frac{YZ}{\rho} \frac{dp}{dx} \quad (9)$$

278 Determining the friction velocity for the rough floor (u_{*f}) can therefore be inferred from
 279 measurements of the pressure gradient ($\frac{dp}{dx}$) by re-arranging Equation 8 as:

280

$$281 \quad u_{*f}^2 = - \left(\frac{2Z}{Y} + 1 \right) u_{*s}^2 - \frac{Z}{\rho} \frac{dp}{dx} \quad (10)$$

282

283 Now u_{*s} can be determined by noting that when $u_{*f} = u_{*s}$, Equation 8 becomes:

$$284 \quad 2(Z + Y)u_{*a}^2 = (2Z + 2Y)u_{*s}^2 \quad (11)$$

285 Equating Equations 7 and 11 gives:

$$286 \quad u_{*s}^2 = - \frac{YZ}{2(Z+Y)\rho} \frac{dp}{dx} \Big|_s \quad (12)$$

287 Where $\frac{dp}{dx} \Big|_s$ denotes the pressure gradient when all four surfaces are smooth. Hence, u_{*f}
 288 can be related to current pressure gradient ($\frac{dp}{dx}$) and the smooth pressure gradient ($\frac{dp}{dx} \Big|_s$) by:

$$289 \quad u_{*f}^2 = - \frac{Z}{\rho} \left[\frac{dp}{dx} - \frac{(2Z+Y)}{2(Z+Y)} \frac{dp}{dx} \Big|_s \right] \quad (13)$$

290 Finally, the surface roughness (Z_0) can be estimated from the central flow characteristics of
 291 the duct:

$$292 \quad Z_0 \approx \frac{25 \times 10^{-3}}{\exp \left(\frac{ku_c}{u_{*f}} \right)} \quad (14)$$

293 where u_c is the measured velocity in the centre of the duct ($z = 25$ mm) and k = von
 294 Karman's constant (0.4).

295 These theoretical workings were tested by measuring the pressure gradient for the
 296 transition and working sections of the tunnel over three test surfaces (under both transition
 297 and working sections). These three surfaces are; smooth (4 mm ABS plastic, 'glassy' side
 298 up), medium (213 micron sand spray-glued to PVC) and rough (bubble-wrap with bubble 10
 299 mm diameter, 5 mm high). Results in Table 1 show that as the test surface roughness
 300 increased, so did u_{*f} , indicating that the pressure gradient method is sensitive to scaling
 301 issues within the MWT. This increases confidence that drag coefficient can be partitioned.

302

303

304 Table 1 Flow descriptors for the MWT calculated using the pressure gradient method (Raupach et al. 2006) for
 305 the flow on the tunnel floor. Wind speeds measured using the roof mounted pressure ports (pressure port
 306 measurements at $x = 200$ and 900 , $y = 50$, $z = 50$).

Tunnel speed m s^{-1}	Test surface	Coefficient of drag (unitless)	u_* (m s^{-1})	z_o (mm)
6.8	Smooth	0.0023	0.32	0.006
6.8	Medium	0.0034	0.40	0.026
6.8	rough	0.0059	0.52	0.139
11.6	Smooth	0.0021	0.54	0.004
11.6	Medium	0.0034	0.68	0.027
11.6	rough	0.0056	0.86	0.117

307
 308 The data in Table 1 compare well with u_* values of 0.35 m s^{-1} ($U=6.8 \text{ m s}^{-1}$) and 0.72 m s^{-1}
 309 ($U=11.6 \text{ m s}^{-1}$) obtained by Shao and Raupach [25] who tested on a bed of $200 \mu\text{m}$ sand
 310 using a large portable wind tunnel. This result suggests that the MWT produces
 311 comparable surface drag for the wind speeds in the tunnel. Figure 4 shows the relationship
 312 between tunnel velocity and friction velocity for the MWT.

313

314
 315 Fig. 4 Relationships between the tunnel velocity and u_* for each of the three tested surfaces (smooth ($z < 0.01 \text{ mm}$),
 316 medium ($z \sim 0.1 \text{ mm}$) and rough ($z \sim 2 \text{ mm}$)). Wind speeds measured using the roof mounted pressure ports
 317 (pressure port measurements at $x = 200$ and 900 , $y = 50$, $z = 50$). All standard errors lie within ± 0.002 of the
 318 mean values

319

320

321 **2.3 Saltation injection, collection efficiency and operation procedures**

322 Saltation injection is used in a wind tunnel to achieve saturated saltation flow. In the field
323 saturated saltation will develop over much longer distances than can be reproduced in the
324 working sections of portable wind tunnels [20, 25]. Saltation sands should therefore be
325 delivered at a flux rate sufficient to produce saltation rates observed in the field, and have
326 known physical properties (size, chemical composition).

327 Commercially available sand with a unimodal size of 213 microns and 99 % quartz content
328 is used in the MWT saltation injection system. Without the tunnel operating (tunnel velocity
329 = 0 ms⁻¹) the saltation flux rate is 6.1±0.1 g m⁻¹s⁻¹. As the tunnel airflow velocity increases
330 (tunnel velocity = 5–16.1 ms⁻¹) so too does the saltation flux rate, ranging from 7.5-10.8 g
331 m⁻¹s⁻¹ (Figure 5). Saltation flux rates are slightly higher than those reported by Pietersma et
332 al. [26] who had an adjustable saltation feed rate of 0.25-6.6 g m⁻¹s⁻¹, but lower than Van
333 Pelt et al., [5] who had an adjustable saltation feed rate of 10-30 g m⁻¹s⁻¹. The range of
334 saltation flux rates for the MWT is within the variability reported for other wind tunnels and
335 therefore differences considered inconsequential.

336

337 **Fig. 5 Saltation flux rate is 6.1 g m⁻¹s⁻¹ with no tunnel flow but increases (7.5-10.8 g m⁻¹s⁻¹) as tunnel velocity**
338 **increases. Each velocity was replicated five times measured using pitot-static tubes at x = 900, y = 50, z = 25 and**
339 **all standard errors lie within +/- 0.07 of the mean values**

340

341 The collection efficiency of the sediment sampler was tested by adding a known amount of
342 saltation sand. The sampler inlet has a cross-section of 10 x 50 mm representing 10 % of

343 the cross-sectional area of the tunnel. For four wind speeds (each repeated five times) 30
 344 g of saltation sand was added via the saltation injection system at the start of the one
 345 minute run (using a smooth test bed). Assuming that the sediment sampler is 100 %
 346 efficient, 3 g of sediment should be collected at the end of each run. The ratio of collected
 347 sediment to that expected shows that on the smooth test surface, the sampling efficiency
 348 was greater than 95 % for wind speeds higher than 10 ms⁻¹ but dropped to 85 % at lower
 349 wind speeds (Figure 6). A change in trapping efficiency with wind speed is commonly
 350 observed in semi-isokinetic samplers [27]. On rough surfaces the expectation is that
 351 sediment will be trapped by roughness elements reducing the amount of sediment reaching
 352 the sampler. Understanding the trap efficiency means that the storage potential of different
 353 surfaces can be estimated [24].

354
 355 **Fig. 6** Collection efficiency of the sediment sampler indicates that over a smooth test surface the tunnel is very
 356 efficient at collecting the expected 10 % sediment flow released in the tunnel at wind speeds greater than 10 m s⁻¹.
 357 The tunnel under samples at tunnel velocities less than 8 m s⁻¹ (baffle position 2). Each velocity was replicated five
 358 times measured using pitot-static tubes within the tunnel flow at x = 900, y = 50, z = 25 and sediment trap line. All
 359 standard errors lie within +/- 0.05 of the mean values

360
 361 Operating the MWT uses two approaches to saltation impact. The first approach relies on
 362 any naturally-available, loose, erodible material to act as a saltation source. Wind-removed
 363 sediment is collected on 125 mm-diameter glass-fibre filter paper with 0.1 µm pores, and
 364 weighed. Sediment flux (Q) (g m⁻¹s⁻¹) with no added saltation material is calculated as:

$$Q = \frac{mass}{[0.01m^2 \times 60s]} \quad (10)$$

The second approach uses the addition of saltation material as described above to initiate the breakdown and removal of fine sediments through abrasion process. Saltation induced sediment flux (Q_{Si}) ($g\ m^{-1}s^{-1}$) is calculated as:

$$Q_{Si} = \frac{[mass - 3g]}{[0.01m^2 \times 60s]} \quad (11)$$

where mass is the weight (g) of sediment collected on the filter paper and $0.01m^2$ is the footprint of the MWT working area. This equation assumes that all the sediment introduced at the upwind end reaches the sediment sampler at the downwind end. This is a reasonable assumption for a smooth surface with no storage capacity. As highlighted above rough surfaces can trap sediments and there is potential to use the MWT to increase the understanding of this however it will not be explored further in this paper. To identify the susceptibility of a surface to abrasion, the ratio of $Q_{Si} : Q$ is used to describe the saltation entrainment ratio, quantifying how much more sediment was lost with the addition of saltation sand. The higher the number the greater impact of the saltation sands.

The use of a range of wind speeds on all surfaces provides an indication of how sediment flux changes with wind speed. Comparison between the surfaces requires a standard wind speed to act as a default comparison. The chosen wind speed was $u = 9\ m\ s^{-1}$ as this typically causes sediment entrainment in the field [28, 29].

2.4 Summary of development and calibration

The MWT has been shown to produce velocities ranging from 5 to $18\ m\ s^{-1}$ with high reproducibility. Wind velocities are laterally uniform ($\pm 0.2\ m\ s^{-1}$) and values of u_{τ} at the tunnel bed (calculated using the integral momentum method) are comparable with those from larger tunnels where logarithmic profiles can be developed [25,5]. To account for the variability in the saltation feed rate as velocity increases, known amounts of saltation sediment were used for all runs. A high collection efficiency (>85 %) was reported across a range of tunnel velocities. The MWT therefore achieves the three fundamental wind tunnel design criteria proposed by Maurer et al., [13] of, producing wind speeds and aerodynamic flows that reflect natural conditions, along with being easy to transport, assemble and operate.

399 3 Research Applications of the MWT

400 The second half of this paper provides three contrasting examples of where the MWT has
401 been used in field research in order to illustrate the practicality of its use.

402

403 3.1 Wind erosion of rangeland soils

404 A field study was undertaken in semi-arid rangelands near Longreach, Queensland,
405 Australia to assess the impact of different stocking pressures from cattle and sheep grazing
406 on soil erodibility to wind [30]. Wind erosion simulations were conducted along a grazing
407 gradient (from high to low) leading away from a stock watering point; following the design of
408 Pickup [31]. Field experiments were conducted on two soil types, a cracking clay soil
409 ($23^{\circ}36'44.8''\text{S}$; $143^{\circ}17'46.9''\text{E}$) and a sandy loam ($30^{\circ}27'14.7''\text{S}$; $141^{\circ}44'32.4''\text{E}$).

410 Both sites were vegetated with annual and perennial grasses. As the focus of the study
411 was upon soil erodibility (rather than the protection to soils afforded by vegetation) it was
412 important to exclude grasses from the wind tunnel simulation sites. The MWT was highly
413 suitable to this application because its small footprint could fit between the grass clumps
414 (Fig. 7). This project would not have been feasible with a conventional field wind tunnel,
415 because grasses could not have been excluded from the large working section of such a
416 tunnel.

417

418 Fig. 7 The micro wind tunnel was highly suitable to deployment in a grassed rangeland site because its small
419 footprint could fit between grass clumps

Sediment flux was measured along the grazing gradient using the MWT, but only two points along this transect are reported here. The highest stocking rate and soil surface disturbance zone was closest to the watering point and a low stocking rate and disturbance zone was 2000 m from the watering point.

Table 2 Measured sediment flux ($\text{g/m}^2/\text{s}$) at two disturbance zones on two soil types using one MWT wind speed, $U = 9 \text{ m s}^{-1}$. Q is sediment flux with only wind blowing across soil surface. Q_{SI} is the sediment flux with saltation sediment added to the tunnel runs

	Sediment flux ($\text{g/m}^2/\text{s}$)			
	Clay site		Sandy loam site	
	High disturbance zone	Low disturbance zone	High disturbance zone	Low disturbance zone
Without saltation added (Q)	3.35	0.04	9.59	2.64
With saltation added (Q_{SI})	5.66	0.31	13.47	3.39
Saltation entrainment ratio ($Q_{\text{SI}} : Q$)	x 1.7	x 7.8	x 1.4	x 1.3

Three results of the MWT simulations are shown in Table 2.

1. Overall wind erosion rates, measured as sediment fluxes (Q), are higher on sandy loam soils than clay soils; confirming the widely reported result that increasing the sand content of soils increases their erodibility [32].

2. Disturbance of soil surfaces increases sediment fluxes on both soils but the relative impact is much greater on the clay soil than on the sandy loam soils. This suggests that clay soils are more vulnerable to increased stocking rates than sandy soils.

3. If saltation sands are present in the windflow sediment fluxes are increased to a much greater extent on clay soils (x 1.7 to x 7.8) than sandy loam soils (x 1.3 to x 1.4); confirming the earlier result that the presence of sands increases soil erodibility.

This study provides new and useful understanding of changes in soil erodibility in response to variations of grazing pressure. The results suggest that spatial variations of soil surface disturbance induced by grazing pressure have a direct impact on soil erodibility to wind. The MWT played a crucial role in this project because its small footprint enabled the positioning of the tunnel between grass clumps; thus testing the soil surface conditions avoiding the complicating effects of vegetation upon wind erosion.

3.2 Wind erosion on alluvial claypans

A field study was undertaken on a claypan on the Diamantina River floodplain, Queensland. Claypans as a single unit (covering from 1 – 100s square kilometres in size) are known to be dust source hotspots [32, 33]. However claypans do not comprise uniform surfaces and instead are characterised by a complex mosaic of surface crust types. The aim of this study

was to determine the relative erodibility of each crust type. The erodibility of individual crust types is poorly understood in part because most large portable wind tunnels cover a range of crust types in a single run, thereby homogenising the results. Field experiments were conducted on three crust types; structural, depositional and biological as defined by Valentin and Bresson [34] and Thomas and Dougill [35]. The MWT was used both without and with saltation added.

Across the claypan, the sediment flux varied considerably (at $u = 9 \text{ m s}^{-1}$), with biological crust surfaces yielding a higher sediment flux (Q) than the depositional and structural crusts (Table 3). Sediment flux with saltation added (Q_{SI}) is again higher from the biological crusts than the structural and depositional (Table 3). At first sight, these results appear to be inconsistent with other published studies [16,17] which conclude that biological crusts provide greater protection to soils than physically crusted or depositional surfaces. In reality the results probably reflect the capacity of biological crusts to store loose sediment and release it when wind speeds increase. The proportional increase in sediment flux with the addition of saltation sands ($Q_{SI} : Q$) is much less for biological crusts (x 5.6) than depositional and structural crusts (x14 and x 16 respectively), indicating that biological crusts are more protective of soils in a saltation impact environment. This result reinforces the earlier interpretation; that the relatively high overall sediment fluxes from biological crusted surfaces reflect their capacity to store loose sediment and release it when wind speeds increase.

This result also supports the conclusions from the study by Hupy [36] which showed that the spatial positioning of different surface types can have an important influence upon overall wind erosion rates from a claypan. Hupy [36] found that storage zones of saltation sands, such as the biological crusted regions, provided a source of abrasion material for downwind sites.

Table 3 Measured sediment flux ($\text{g/m}^2/\text{s}$) at three surface crust types using one MWT wind speed, $U = 9 \text{ m s}^{-1}$

	Sediment flux ($\text{g/m}^2/\text{s}$)		
	Structural crust	Depositional crust	Biological crust
Without saltation added (Q)	0.109	0.316	1.117
With saltation added (Q_{SI})	1.766	4.371	6.196
Saltation entrainment ratio ($Q_{SI} : Q$)	x 16	x 14	x 5.6

This study provides new and useful understanding of the changes in soil erodibility across a heterogenous claypan surface. The results suggest that spatial variations of crust types have a direct impact on erodibility and that both the abundance and spatial distribution of the crust types have an effect of the overall sediment flux of a claypan as a whole. The use of the MWT was crucial to the collection of this sediment flux data as its small nature and portability enabled the testing of discrete crust types. Larger field tunnels would have measured the response of either a range of crust types, and/or the patchy vegetation which is commonly associated with the biological crusts on claypans.

485

486 3.3 Erodibility of iron ore sediments

487 A field study was undertaken to assess the relative erodibility of different iron ore sediments
488 within an iron ore port facility in Western Australia. The iron ore storage facility involved
489 receiving, sorting, stacking, transporting via conveyors and ship loading several different
490 ore products. This diverse range of products and material handling activities produced
491 considerable fugitive dust which can have negative impacts upon local communities. The
492 term fugitive dust refers to dust which is mechanically entrained [37] and may be wind-
493 eroded at mine sites, ore storage areas and mine rehabilitation areas [38, 39]. One
494 measure of the fugitive dust potential of an ore deposit is the surface sediment fluxes
495 resulting from increased wind speeds. Identifying the key sources of dust is an important
496 precursor to applying appropriate dust mitigation strategies. The MWT was used to
497 measure the wind erodibility of different iron ore deposits. MWT measurements were
498 carried out on two iron ore stockpiles and two local ore deposits; on roadsides and beneath
499 the conveyor belts (Table 4).

500

501 **Table 4. Measured sediment flux ($\text{g/m}^2/\text{s}$) at two iron ore sites and two deposited sediment sites using one MWT**
502 **wind speed, $U = 9 \text{ m s}^{-1}$**

	Sediment flux ($\text{g/m}^2/\text{s}$)			
	Iron Ore surfaces		Deposited sediments	
	Stockpile 1	Stockpile 2	Deposits on road	Deposits below conveyor
Without saltation added (Q)	1.41	0.01	78.13	4.35
With saltation added (Q_{SI})	2.65	0.49	159.08	32.93
Saltation entrainment ratio ($Q_{\text{SI}} : Q$)	x 1.9	x 49.0	x 2.0	x 7.5

503

504 The highest overall sediment fluxes were recorded on the local ore deposits (on road and
505 under conveyor) and the lowest from the two stockpile ores (Table 4). The very high fluxes
506 on the local ore deposits arose because they were relatively fine dust deposits ($< 50 \mu\text{m}$),
507 with low compaction. These deposits were therefore a major potential source of fugitive
508 dusts. The sediment fluxes with saltation material in the airflow (Q_{SI}) were increased on all
509 sites. While the proportional increase in sediment flux ($Q_{\text{SI}} : Q$) was greatest on the
510 stockpile 2, the absolute sediment flux was much lower than on the local deposits. The
511 large range in sediment fluxes between sites highlights the complexity of managing fugitive
512 dust emissions at mine sites and iron ore storage areas and the need to adopt a range of
513 different dust mitigation strategies.

514

515 The MWT proved to be very well suited to the practical demands of operating at this
516 industrial site; where equipment access and operation was difficult, especially on inclined
517 stockpile surfaces and beneath conveyor belts.

518 519 **3.4 Summary of applications of the micro wind tunnel**

520 The MWT has proved to be a valuable tool for assessing small scale soil erodibility issues.
521 The use of the MWT across a range of surfaces provides new and useful understanding of
522 the erodibility of rangelands, claypans and ore stockpiles. There are 3 key attributes of the
523 MWT. First, nimbleness, second flexibility, third operability. The MWT “nimbleness” in
524 getting in and around grass clumps which are a common feature of many rangelands and
525 difficult to measure with larger tunnels provides a true practical advantage. The tunnel is
526 “flexible” in being easily deployed across diverse terrains and in constricted industrial
527 settings. Truck or trailer mounted portable wind tunnels are well suited to large open
528 agricultural paddocks, therefore to apply these tools in a spatially restricted environment
529 often means the test surfaces have to be disturbed and brought to the tunnel, thus altering
530 their natural erodibility properties. Another important feature of the MWT is its “operability”.
531 This tunnel can be used, packed up and transported by one person. Larger portable tunnels
532 require multiple people and often heavy lifting aids to assemble and pack the equipment.

533 534 **4 Conclusion**

535 The micro wind tunnel (MWT) is a small, portable wind tunnel, operable by one person.
536 The MWT produces airflow velocities ranging from 5 to 18 m s⁻¹ with high reproducibility.
537 The velocity profiles show an orderly progression downwind, and the across tunnel contour
538 plots showed a good air speed distribution. Unlike larger wind tunnels, the dimensions of
539 the MWT limit the form of velocity distribution in the working section, but it is these duct like
540 dimensions that enable the shear stress within to be determined from the pressure drop.
541 Through measuring the pressure gradients enables the measurement of drag coefficient
542 and allows the calculation of both sensible u_* and surface-roughness measures in the
543 MWT. Saltation feed into the airflow is at the optimal rate of 6.1 g m⁻¹s⁻¹ and collection
544 efficiency is high.

545 The utility of the MWT is demonstrated from wind erosion studies on rangelands and
546 alluvial claypans, and at an iron ore storage facility. The rangeland study highlights the
547 ease of use of the MWT on surfaces with complex patterns of tufted pasture grasses. At
548 the claypan site the small footprint of the MWT allowed wind erosion simulations to be
549 conducted on different discrete surface crust types. At the iron ore storage facility the MWT
550 proved to be very well suited to the practical demands of operating at an industrial site;
551 where equipment access and operation were difficult; on inclined stockpile surfaces and
552 beneath conveyor belts. The MWT is therefore a valuable wind erosion simulation tool
553 which very well supplements larger portable field wind tunnels.

554

555

556 **Acknowledgements**

557 The authors acknowledge the major contribution to the design and construction of the MWT
558 by their late co-author Mike Raupach who passed away recently. Mike's passing is a great
559 loss to our research community. Thanks to Samantha McMillan for initial testing and
560 development work on the MWT. This work was partially funded by the UK NERC
561 (NE/K011461/1) and Griffith University.

562

563 **Reference**

- 564 1. Leys JF (1999) Wind Erosion on Agricultural Land. *In 'Aeolian Environments, Sediments*
565 *and Landforms'*. (Eds. Gouldie, A. S., Livingstone, I., and Stokes, S.), pp. 143-166 (John
566 Wiley and Sons).
- 567 2. Webb NP, Strong CL (2011) Soil erodibility dynamics and its representation for wind
568 erosion and dust emission models. *Aeolian Research* 3:165-179
- 569 3. Zobeck TM (1991) Abrasion of crusted soils: Influence of abrader flux and soil properties.
570 *SSSAJ*. 55(4): 1091-1097
- 571 4. Goossens D, and Offer ZY (2000) Wind tunnel and field calibration of six Aeolian dust
572 samplers. *Atmospheric Environment*. 34(7): 1043-1057
- 573 5. Van Pelt RS, Zobeck TM, Baddock MC, Cox JJ (2010) Design, construction and
574 calibration of a portable boundary layer wind tunnel for field use. *Transactions of the*
575 *American Society of Agricultural and Biological Engineers* 53(5):1-10
- 576 6. Etyemezian V, Nikolich G, Ahonen S, Pitchford M, Sweeney M, Gillies J and Kuhns H
577 (2007) The Portable In-Situ Wind Erosion Laboratory (PI-SWERL): A new method to
578 measure windblown dust properties and potential for emissions *Atmos Environ* 41:3789–
579 3796
580
- 581 7. Hagen LJ (2004) Evaluation of the Wind Erosion Prediction System (WEPS) erosion
582 submodel on cropland fields. *Environmental Modelling and Software* 19: 171–176
- 583 8. Webb NP, McGowan HA, (2009) Approaches to modelling land erodibility by wind.
584 *Progress in Physical Geography* 33:587–613
- 585 9. Butler HJ, Hogarth WL, and McTainsh GH (1996) A source-based model for describing
586 dust concentrations during wind erosion events: an initial study. *Environmental Software*
587 11(1-3):45-52
- 588 10. Bagnold RA (1941) The physics of blown sand and desert dunes. William Morrow &
589 Company, New York

- 590 11. Chepil WS (1953) Field structure of cultivated soils with special reference to erodibility
591 by wind. Soil Science Society Proceedings 185-190
- 592
- 593 12. Zhang YM, Wang HL, Wang XQ, Yang WK and Zhang DY (2006) The microstructure of
594 microbiotic crust and its influence on wind erosion for a sandy soil surface in the
595 Gurbantunggut Desert of Northwestern China. Geoderma 132:441–449
- 596
- 597 13. Maurer T, Hermann L, Gaiser T, Mounkaila M, Stahr K (2006) A mobile wind tunnel for
598 wind erosion field measurements. Journal of Arid Environments 66(2):257-271
- 599 14. Nickling WG and Gillies JA (1993) Dust emission and transport in the Male, West Africa.
600 Sedimentology 40:859-868
- 601
- 602 15. Gillette DA (1978) Tests with a portable wind tunnel for determining wind erosion
603 threshold velocities. Atmospheric Environment 12:2309-2313
- 604 16. Belnap J and Gillette DA (1997) Disturbance of biological soil crusts: impacts on
605 potential wind erodibility of sandy desert soils in southeastern Utah. Land Degradation
606 and Development 8:355-362
- 607 17. Belnap, J. and Gillette, DA (1998) Vulnerability of desert biological soil crusts to wind
608 erosion: the influences of crust development, soil texture, and disturbance. Journal of
609 Arid Environments 39:133-142
- 610
- 611 18. Sweeney M, Etyemezian V, Macpherson T, Nickling W, Gillies J, Nikolich G, McDonald
612 E (2008) Comparison of PI-SWERL with dust emission measurements from a straight-
613 line field wind tunnel. Journal of Geophysical Research 113:(F01012)
614 doi:10.1029/2007/JF000830
- 615 19. Zingg AW (1951) A portable wind tunnel and dust collector development to evaluate the
616 erodibility of field surfaces. Agronomy Journal 43(2):189-191
- 617 20. Raupach MR and Leys JF (1990) Aerodynamics of a portable wind erosion tunnel for
618 measuring soil erodibility by wind. Australian Journal of Soil Research 28(2):177-191
- 619 21. White FM (1994) Fluid Mechanics. McGraw-Hill, New York
- 620 22. Schetz JA and Fuhs AE (1999) Fundamentals of fluid mechanics. John Wiley and Sons,
621 New York
- 622 23. Batchelor GK (1967) An Introduction to Fluid Dynamics. Cambridge University Press,
623 Cambridge
- 624
- 625 24. Raupach MR, Hughes DE and Cleugh HA (2006) Momentum absorption in rough-wall
626 boundary layers with sparse roughness elements in random and clustered distributions.
627 Boundary-Layer Meteorology 120:201-218

- 628 25. Shao Y and Raupach MR (1992) The overshoot and equilibration of saltation. Journal of
629 Geophysical Research 97(20):559-564
- 630 26. Pietersma D, Stetler LD and Saxton KE (1996) Design and aerodynamics of a portable
631 wind tunnel for soil erosion and fugitive dust research. Trans of the ASAE 39:2075-2083
- 632 27. Goossens D and Offer ZY (2000) Wind Tunnel and field calibration of six Aeolian dust
633 samplers. Atmospheric Environment 12(12):1043-1057
634
- 635 28. McTainsh GH, Leys JF, and Nickling WG (1999) Wind erodibility of arid lands in the
636 channel country of Western Queensland, Australia. Zeitschrift fur geomorphologie
637 116:113-130
- 638 29. Gillette DA, Adams J, Muhs D and Kihl R (1982) Threshold friction velocities and
639 rupture moduli for crusted desert soils for the input of soil particles into the air. Journal
640 of Geophysical Research 87:9003-15
- 641 30. Aubault HA (2014) Estimating the impacts of pastoral activities upon wind erosion in the
642 arid and semi-arid rangelands of eastern Australia. Ph.D. Thesis, Griffith University
- 643 31. Pickup G (1989) New land degradation survey techniques for arid Australia: problems
644 and prospects. Aust. Rangel. J. 11:74-82.
645
- 646 32. McTainsh GH and Leys JF (1993) "Chapter 7 - Wind erosion". In: McTainsh GH and
647 Boughton WC (Eds) Land degradation processes in Australia. Longman-Cheshire,
648 Melbourne pp188-233
- 649 33. Reheis MC (2006) A 16-year record of eolian dust in Southern Nevada and California,
650 USA: controls on dust generation and accumulation. Journal of Arid Environments
651 67:487-520
- 652
- 653 34. Valentin C and Bresson LM (1992) Morphology, genesis and classification of
654 surface crusts in loamy and sandy soils. Geoderma 55:225-245.
655
- 656 35. Thomas AD and Dougill AJ (2006) Distribution and characteristics of cyanobacterial soil
657 crusts in the Molopo Basin, South Africa. Journal of Arid Environments 64:270-283
658
- 659 36. Hupy JP (2004) Influence of vegetation cover and crust type on wind-blown sediment in
660 a semi-arid climate. Journal of Arid Environments 58:167-179
- 661 37. Gillies JA, Watson JG, Rogers CF, Dubois D, Chow JC, Langston R, and Sweet J (1999)
662 Long-Term Efficiencies of Dust Suppressants to Reduce PM 10 Emissions from
663 Unpaved Roads. Journal of the Air & Waste Management Association 49:3-16
664
- 665 38. Cowherd C Jr, Bohn R and Cuscino T (1979) Iron and steel plant open source fugitive
666 emission evaluation; Report No EPA-600/2-79-103. Research Triangle Park, NC, U.S.
667 Environmental Protection Agency, Industrial Environmental Research Laboratory
668

- 669 39. Chan Kon L, Durucan S and Korre A (2007) The development and application of a wind
670 erosion model for the assessment of fugitive dust emissions from mine tailings dumps.
671 International Journal of Mining, Reclamation and Environment 21(3):198-218
672
673