SUPPLEMENTAL DATA

Solid-state amorphization of rebamipide milling and investigation on solubility and stability of the amorphous form

Xinnuo Xiong, Kailin Xu, Shanshan Li, Peixiao Tang, Ying Xiao, Hui Li*

College of Chemical Engineering, Sichuan University, Chengdu 610065, China

*Corresponding author. Address: College of Chemical Engineering, Sichuan University, Chengdu 610065, China. **Tel.:** +86 028 85405149; **Fax:** +86 028 85401207. **E-mail address:** lihuilab@sina.com(Hui Li)

Figure S1. XRD patterns of the RBM that recrystallized from milled and spray dried RBM upon heating.

Figure S2. Stability of spray dried RBM monitored at 50 °C using XRPD.

Figure S3. XRPD patterns of spray dried RBM under (a) 84.3% RH for 9 d, (b) 97.3% RH for 12 h, (c) 97.3% RH for 24 h, and (d) 97.3% RH for 9 d, and spray dried RBM-PVP under (e) 84.3% RH for 9 d, (f) 97.3% RH for 12 h, (g) 97.3% RH for 24 h, and (h) 97.3% RH for 9 d.

Figure S4. (a) XRPD patterns, (b) DSC curves, and (c) magnified DSC curves of milled amorphous RBM monitored under 97.3% RH.