Contents lists available at SciVerse ScienceDirect

Journal of Petroleum Science and Engineering

journal homepage: www.elsevier.com/locate/petrol

The flow of power-law fluids in axisymmetric corrugated tubes

Taha Sochi

Imaging Sciences & Biomedical Engineering, King's College London, The Rayne Institute, St Thomas' Hospital, London, SE1 7EH, UK

ARTICLE INFO

Article history:

Received 9 November 2010

Accepted 8 August 2011

Available online 19 August 2011

Keywords:

Non-newtonian flow

Power-law fluid

Corrugated tube

Axisymmetric

ABSTRACT

In this article we present an analytical method for deriving the relationship between the pressure drop and flow rate in laminar flow regimes, and apply it to the flow of power-law fluids through axially-symmetric corrugated tubes. The method, which is general with regard to fluid and tube shape within certain restrictions, can also be used as a foundation for numerical integration where analytical expressions are hard to obtain due to mathematical or practical complexities. Five converging–diverging geometries are used as examples to illustrate the application of this method.

© 2011 Elsevier B.V. All rights reserved.

1. Introduction

Modeling the flow in corrugated tubes is required for a number of technological and industrial applications. Moreover, it is a necessary condition for correct description of several phenomena such as yield-stress, viscoelasticity and the flow of Newtonian and non-Newtonian fluids through porous media (Pilitsis and Beris, 1989; Sochi, 2009, 2010a, 2010b, 2010c, 2010d; Talwar and Khomami, 1992). In the literature of fluid mechanics there are numerous studies on the flow through tubes or channels of corrugated nature. Most of these studies use numerical techniques such as spectral and finite difference methods (Burdette et al., 1989; James et al., 1990; Lahbabi and Chang, 1986; Momeni-Masuleh and Phillips, 2004; Phan-Thien and Khan, 1987; Phan-Thien et al., 1985; Pilitsis and Beris, 1989, 1992). Some others adopt analytical approaches based on simplified assumptions and normally deal with very special cases (Oka, 1973; Williams and Javadpour, 1980). The current paper presents a mathematical method for deriving analytical relations between the volumetric flow rate and pressure drop in corrugated circular capillaries of variable cross section, such as those illustrated schematically in Fig. 1. It also presents five examples in which this method is used to derive flow equations for non-Newtonian fluids of power-law rheology. The method, however, is more general and can be used for other tube shapes and other rheologies. The following derivations assume a laminar flow of a purely-viscous incompressible fluid where the tube corrugation is smooth and relatively small to avoid complex flow phenomena which are not accounted for in the underlying assumptions of this method.

2. P–Q relation for power-law fluids

The power-law, or Ostwald-de Waele, is a widely-used fluid model to describe the rheology of shear thinning fluids. It is one of the simplest time-independent non-Newtonian models as it contains two parameters only. The model is given by the relation (Bird et al., 1987; Carreau et al., 1997)

$$\mu = \frac{\tau}{\dot{\gamma}} = C\dot{\gamma}^{n-1} \quad (1)$$

where μ is the fluid viscosity, τ is the stress, $\dot{\gamma}$ is the strain rate, C is the consistency factor, and n is the flow behavior index. In Fig. 2 the bulk rheology of this model for shear-thinning case is presented generically on log–log scales. Although the power-law is used to model shear-thinning fluids, it can also be used for modeling shear-thickening by making n greater than unity. The major weakness of power-law model is the absence of plateaux at low and high strain rates. Consequently, it fails to produce sensible results in these flow regimes.

The volumetric flow rate, Q , of a power law fluid through a circular capillary of constant radius r with length x across which a pressure drop P is applied is given by

$$Q = \frac{\pi n r^4 P^{1/n}}{2x C^{1/n} (3n + 1)} \left(\frac{2x}{r} \right)^{1-1/n} \quad (2)$$

A derivation of this relation, which can be obtained from Eq. (1), can be found in Appendix A. On solving this equation for P the following relation is obtained

$$P = \frac{2CQ^n(3n + 1)^n x}{\pi^n n^n r^{3n + 1}} \quad (3)$$

E-mail address: taha.sochi@kcl.ac.uk.

Fig. 1. Profiles of converging-diverging axisymmetric capillaries.

For an infinitesimal length, δx , of a capillary, the infinitesimal pressure drop for a given flow rate Q is

$$\delta P = \frac{2CQ^n(3n+1)^n \delta x}{\pi^n n^n r^{3n+1}}. \quad (4)$$

For an incompressible fluid, the volumetric flow rate across an arbitrary cross section of the capillary is constant. Therefore, the total pressure drop across a capillary of length L with circular cross section of varying radius, $r(x)$, is given by

$$P = \frac{2CQ^n(3n+1)^n}{\pi^n n^n} \int_0^L \frac{dx}{r^{3n+1}}. \quad (5)$$

In the following sections, Eq. (5) will be used to derive analytical expressions for the relation between pressure drop and volumetric flow rate for five converging-diverging geometries of axially-symmetric pipes. The method can be equally applied to other geometries as long as the tube radius can be expressed analytically as a function of the tube axial distance.

2.1. Conic tube

For a corrugated tube of conic shape, depicted in Fig. 3, the radius r as a function of the axial coordinate x in the designated frame is given by

$$r(x) = a + b|x| \quad -L/2 \leq x \leq L/2 \quad a, b > 0 \quad (6)$$

Fig. 2. The bulk rheology of power-law fluids on logarithmic scales for finite strain rates ($\dot{\gamma} > 0$).

Fig. 3. Schematic representation of the radius of a conically shaped converging-diverging capillary as a function of the distance along the tube axis.

where

$$a = R_{min} \quad \text{and} \quad b = \frac{2(R_{max} - R_{min})}{L}. \quad (7)$$

Hence, Eq. (5) becomes

$$P = \frac{2CQ^n(3n+1)^n}{\pi^n n^n} \int_{-L/2}^{L/2} \frac{dx}{(a + b|x|)^{3n+1}} \quad (8)$$

$$= \frac{2CQ^n(3n+1)^n}{\pi^n n^n} \left(\left[\frac{1}{3bn(a-bx)^{3n}} \right]_{-L/2}^0 + \left[-\frac{1}{3bn(a+bx)^{3n}} \right]_0^{L/2} \right) \quad (9)$$

$$= \frac{4CQ^n(3n+1)^n}{3\pi^n n^n + 1b} \left[\frac{1}{a^{3n}} - \frac{1}{(a + bL/2)^{3n}} \right] \quad (10)$$

that is

$$P = \frac{2LCQ^n(3n+1)^n}{3\pi^n n^n + 1(R_{max} - R_{min})} \left[\frac{1}{R_{min}^{3n}} - \frac{1}{R_{max}^{3n}} \right]. \quad (11)$$

2.2. Parabolic tube

For a tube of parabolic profile, depicted in Fig. 4, the radius is given by

$$r(x) = a + bx^2 \quad -L/2 \leq x \leq L/2 \quad a, b > 0 \quad (12)$$

where

$$a = R_{min} \quad \text{and} \quad b = \left(\frac{2}{L}\right)^2 (R_{max} - R_{min}). \quad (13)$$

Therefore, Eq. (5) becomes

$$P = \frac{2CQ^n(3n+1)^n}{\pi^n n^n} \int_{-L/2}^{L/2} \frac{dx}{(a + bx^2)^{3n+1}} \quad (14)$$

$$= \frac{2CQ^n(3n+1)^n}{\pi^n n^n a} \left[x \left(\frac{bx^2}{a} + 1 \right)^{3n} {}_2F_1 \left(\frac{1}{2}, 3n+1; \frac{3}{2}; -\frac{bx^2}{a} \right) \right]_{-L/2}^{L/2} \quad (15)$$

Fig. 4. Schematic representation of the radius of a converging-diverging capillary with a parabolic profile as a function of the distance along the tube axis.

Fig. 5. Schematic representation of the radius of a converging-diverging capillary with a sinusoidal profile as a function of the distance along the tube axis.

where ${}_2F_1$ is the hypergeometric function. Therefore

$$P = \frac{2LCQ^n(3n+1)^n}{\pi^n n^n R_{min}^{3n+1}} {}_2F_1\left(\frac{1}{2}, 3n+1; \frac{3}{2}; 1 - \frac{R_{max}}{R_{min}}\right). \quad (16)$$

2.3. Hyperbolic tube

For a tube of hyperbolic profile, similar to the profile in Fig. 4, the radius is given by

$$r(x) = \sqrt{a + bx^2} \quad -L/2 \leq x \leq L/2 \quad a, b > 0 \quad (17)$$

where

$$a = R_{min}^2 \quad \text{and} \quad b = \left(\frac{2}{L}\right)^2 (R_{max}^2 - R_{min}^2). \quad (18)$$

Therefore, Eq. (5) becomes

$$P = \frac{2CQ^n(3n+1)^n}{\pi^n n^n} \int_{-L/2}^{L/2} \frac{dx}{(a + bx^2)^{(3n+1)/2}} \quad (19)$$

$$= \frac{2CQ^n(3n+1)^n}{\pi^n n^n} \left[x \left(\frac{bx^2}{a} + 1 \right)^{\frac{3n+1}{2}} {}_2F_1\left(\frac{1}{2}, \frac{3n+1}{2}; \frac{3}{2}; -\frac{bx^2}{a}\right) \right]_{-L/2}^{L/2} \quad (20)$$

where ${}_2F_1$ is the hypergeometric function. Therefore

$$P = \frac{2LCQ^n(3n+1)^n}{\pi^n n^n R_{min}^{3n+1}} {}_2F_1\left(\frac{1}{2}, \frac{3n+1}{2}; \frac{3}{2}; 1 - \frac{R_{max}^2}{R_{min}^2}\right). \quad (21)$$

2.4. Hyperbolic cosine tube

For a tube of hyperbolic cosine profile, similar to the profile in Fig. 4, the radius is given by

$$r(x) = a \cosh(bx) \quad -L/2 \leq x \leq L/2 \quad a > 0 \quad (22)$$

where

$$a = R_{min} \quad \text{and} \quad b = \frac{2}{L} \operatorname{arccosh}\left(\frac{R_{max}}{R_{min}}\right). \quad (23)$$

Hence, Eq. (5) becomes

$$P = \frac{2CQ^n(3n+1)^n}{\pi^n n^n a^{3n+1}} \int_{-L/2}^{L/2} \frac{dx}{\cosh^{3n+1}(bx)} \quad (24)$$

$$= \frac{2CQ^n(3n+1)^n}{3\pi^n n^n + 1 a^{3n+1b}} \left[\frac{\sinh(bx)}{\cosh^{3n}(bx) \sqrt{-\sinh^2(bx)}} {}_2F_1\left(\frac{1}{2}, -\frac{3n}{2}; \frac{2-3n}{2}; \cosh^2(bx)\right) \right]_{-L/2}^{L/2}. \quad (25)$$

On evaluating the last expression and taking its real part which is physically significant, the following relation is obtained

$$P = \frac{2LCQ^n(3n+1)^n}{3\pi^n n^n + 1 R_{min} R_{max}^{3n} \operatorname{arccosh}\left(\frac{R_{max}}{R_{min}}\right)} \operatorname{Im}\left({}_2F_1\left(\frac{1}{2}, -\frac{3n}{2}; \frac{2-3n}{2}; \frac{R_{max}^2}{R_{min}^2}\right)\right) \quad (26)$$

where $\operatorname{Im}({}_2F_1)$ is the imaginary part of the hypergeometric function.

2.5. Sinusoidal tube

For a tube of sinusoidal profile, depicted in Fig. 5, where the tube length L spans one complete wavelength, the radius is given by

$$r(x) = a - b \cos(kx) \quad -L/2 \leq x \leq L/2 \quad a > b > 0 \quad (27)$$

where

$$a = \frac{R_{max} + R_{min}}{2} \quad b = \frac{R_{max} - R_{min}}{2} \quad \& \quad k = \frac{2\pi}{L} \quad (28)$$

Hence, Eq. 5 becomes

$$P = \frac{2CQ^n(3n+1)^n}{\pi^n n^n} \int_{-L/2}^{L/2} \frac{dx}{[a - b \cos(kx)]^{3n+1}} \quad (29)$$

$$= -\frac{2CQ^n(3n+1)^n}{3\pi^n n^n + 1 k} \left[\frac{1}{\sin(kx)[a - b \cos(kx)]^{3n}} \sqrt{\frac{-\sin^2(kx)}{a^2 - b^2}} \mathfrak{A} \right]_{-L/2}^{L/2} \quad (30)$$

where $\mathfrak{A}$ is the Appell hypergeometric function given by

$$\mathfrak{A} = F_1\left(-3n; \frac{1}{2}, \frac{1}{2}; 1-3n; \frac{a-b \cos(kx)}{a+b}, \frac{a-b \cos(kx)}{a-b}\right). \quad (31)$$

On taking the limit as $x \rightarrow -\frac{L}{2}^+$ and $x \rightarrow \frac{L}{2}^-$ and considering the real part, the following relation is obtained

$$P = \frac{2LCQ^n(3n+1)^n}{3\pi^n + 1 n^n + 1 R_{max}^{3n} \sqrt{R_{max} R_{min}}} \operatorname{Im}\left(F_1\left(-3n; \frac{1}{2}, \frac{1}{2}; 1-3n; 1, \frac{R_{max}}{R_{min}}\right)\right) \quad (32)$$

where $\operatorname{Im}(F_1)$ is the imaginary part of the Appell hypergeometric function.

It is noteworthy that all these relations (i.e. Eqs. (11), (16), (21), (26) and (32)), are dimensionally consistent. Moreover, they have been thoroughly tested and validated by numerical integration.

3. Conclusions

In this article an approximate mathematical method for obtaining analytical relations between the flow rate and pressure drop in axisymmetric corrugated tubes is presented and applied to the flow of power-law fluids. The method is illustrated by five examples of circular capillaries with converging-diverging shape. This method can be used to derive similar relations for other types of fluid and other types of tube geometry. It can also be used as a base for numerical integration where analytical relations are difficult to obtain due to mathematical or practical reasons. There are many scientific and industrial applications that can benefit from the use of the derived expressions and the underlying method as a good approximation in various practical situations such as modeling the flow in non-uniform ducts or porous media.

Nomenclature

$\dot{\gamma}$	strain rate (s^{-1})
μ	fluid viscosity (Pa.s)
τ	stress (Pa)
C	consistency factor (Pa.s ⁿ)
F_1	Appell hypergeometric function
${}_2F_1$	hypergeometric function
L	tube length (m)
n	flow behavior index
P	pressure drop (Pa)
Q	volumetric flow rate ($m^3.s^{-1}$)
r	tube radius (m)
R_{max}	maximum radius of corrugated tube (m)
R_{min}	minimum radius of corrugated tube (m)
x	axial coordinate (m)

Appendix A. Flow rate of power-law fluid in cylindrical tube

In this appendix, we derive an analytical expression for the volumetric flow rate in a cylindrical duct, with inner radius r and length x , assuming a power-law flow. We apply the well-known general result, sometimes called the Weissenberg–Rabinowitsch equation or Rabinowitsch–Mooney equation (Bird et al., 1987; Liu and Masliyah, 1998) which relates the flow rate Q and the shear stress at the tube wall τ_w for laminar flow of time-independent fluids in a cylindrical tube. This equation, which can be derived considering the volumetric flow rate through a differential annulus between r' and $r' + dr'$, is given by (Bird et al., 1987; Carreau et al., 1997; Skelland, 1967; Sochi, 2007; Sochi and Blunt, 2008)

$$\frac{Q}{\pi r^3} = \frac{1}{\tau_w^3} \int_0^{\tau_w} \tau^2 \dot{\gamma} d\tau. \quad (33)$$

For power-law fluids

$$\tau = C\dot{\gamma}^n \quad (34)$$

and hence the strain rate is given by

$$\dot{\gamma} = \frac{\tau^{1/n}}{C^{1/n}}. \quad (35)$$

On substituting this relation into Eq. (33), the following is obtained

$$\frac{Q}{\pi r^3} = \frac{1}{\tau_w^3 C^{1/n}} \int_0^{\tau_w} \tau^{2+1/n} d\tau \quad (36)$$

i.e.

$$Q = \frac{\pi r^3}{\tau_w^3 C^{1/n} (3 + 1/n)} \left[\tau^{3+1/n} \right]_0^{\tau_w} = \frac{\pi r^3 \tau_w^{3+1/n}}{\tau_w^3 C^{1/n} (3 + 1/n)} = \frac{\pi r^3 \tau_w^{1/n}}{C^{1/n} (3 + 1/n)}. \quad (37)$$

Since

$$\tau_w = \frac{Pr}{2x} \quad (38)$$

we obtain

$$Q = \frac{\pi r^3}{C^{1/n} (3 + 1/n)} \left(\frac{Pr}{2x} \right)^{1/n} = \frac{\pi n r^3 P^{1/n}}{C^{1/n} (3n + 1)} \left(\frac{r}{2x} \right)^{1/n} \quad (39)$$

$$= \frac{\pi n r^4 P^{1/n}}{2x C^{1/n} (3n + 1)} \left(\frac{2x}{r} \right) \left(\frac{2x}{r} \right)^{-1/n} \quad (40)$$

that is

$$Q = \frac{\pi n r^4 P^{1/n}}{2x C^{1/n} (3n + 1)} \left(\frac{2x}{r} \right)^{1-1/n} \quad (41)$$

as given by Eq. (2).

References

- Bird, R.B., Armstrong, R.C., Hassager, O., 1987. second edition. Dynamics of Polymeric Liquids, 1. John Wiley & Sons.
- Burdette, S.R., Coates, P.J., Armstrong, R.C., Brown, R.A., 1989. Calculations of viscoelastic flow through an axisymmetric corrugated tube using the explicitly elliptic momentum equation formulation (EEME). J. Non-Newtonian Fluid Mech. 33 (1), 1–23.
- Carreau, P.J., De Kee, D., Chhabra, R.P., 1997. Rheology of Polymeric Systems. Hanser Publishers.
- James, D.F., Phan-Thien, N., Khan, M.M.K., Beris, A.N., Pilitsis, S., 1990. Flow of test fluid M1 in corrugated tubes. J. Non-Newtonian Fluid Mech. 35 (2–3), 405–412.
- Lahbabi, A., Chang, H.-C., 1986. Flow in periodically constricted tubes: transition to inertial and nonsteady flows. Chem. Eng. Sci. 41 (10), 2487–2505.
- Liu, S., Masliyah, J.H., 1998. On non-Newtonian fluid flow in ducts and porous media – optical rheometry in opposed jets and flow through porous media. Chem. Eng. Sci. 53 (6), 1175–1201.
- Momeni-Masuleh, S.H., Phillips, T.N., 2004. Viscoelastic flow in an undulating tube using spectral methods. Comput. Fluids 33 (8), 1075–1095.
- Oka, S., 1973. Pressure development in a non-Newtonian flow through a tapered tube. Rheol. Acta 12 (2), 224–227.
- Phan-Thien, N., Khan, M.M.K., 1987. Flow of an Oldroyd-type fluid through a sinusoidally corrugated tube. J. Non-Newtonian Fluid Mech. 24 (2), 203–220.
- Phan-Thien, N., Goh, C.J., Bush, M.B., 1985. Viscous flow through corrugated tube by boundary element method. J. Appl. Math. Phys. (ZAMP) 36 (3), 475–480.
- Pilitsis, S., Beris, A.N., 1989. Calculations of steady-state viscoelastic flow in an undulating tube. J. Non-Newtonian Fluid Mech. 31 (3), 231–287.
- Pilitsis, S., Beris, A.N., 1992. Pseudospectral calculations of viscoelastic flow in a periodically constricted tube. Comput. Meth. Appl. Mech. Eng. 98 (3), 307–328.
- Skelland, A.H.P., 1967. Non-Newtonian Flow and Heat Transfer. John Wiley and Sons Inc.
- T. Sochi. Pore-scale modeling of non-Newtonian flow in porous media. PhD thesis, Imperial College London, 2007.
- Sochi, T., 2009. Pore-scale modeling of viscoelastic flow in porous media using a Bautista–Manero fluid. Int. J. Heat Fluid Flow 30 (6), 1202–1217.
- Sochi, T., 2010a. Modelling the flow of yield-stress fluids in porous media. Transp. Porous Media 85 (2), 489–503.
- Sochi, T., 2010b. Non-Newtonian flow in porous media. Polymer 51 (22), 5007–5023.
- Sochi, T., 2010c. Computational techniques for modeling non-Newtonian flow in porous media. Int. J. Model. Simul. Sci. Comput. 1 (2), 239–256.
- Sochi, T., 2010d. Flow of non-Newtonian fluids in porous media. J. Polym. Sci. B 48 (23), 2437–2467.
- Sochi, T., Blunt, M.J., 2008. Pore-scale network modeling of Ellis and Herschel–Bulkley fluids. J. Petrol. Sci. Eng. 60 (2), 105–124.
- Talwar, K.K., Khomami, B., 1992. Application of higher order finite element methods to viscoelastic flow in porous media. J. Rheol. 36 (7), 1377–1416.
- Williams, E.W., Javadpour, S.H., 1980. The flow of an elastico-viscous liquid in an axisymmetric pipe of slowly varying cross-section. J. Non-Newtonian Fluid Mech. 7 (2–3), 171–188.