Package 'CrossScreening'

March 20, 2017

Type Package

Title Cross-Screening in Observational Studies that Test Many Hypotheses

Version 0.0.1

Date 2017-03-20

Description Cross-screening is a new method that uses both random halves of the sample to screen and test many hypotheses. It generally improves statistical power in observational studies when many hypotheses are tested simultaneously.

Imports stats, sensitivitymw, parallel, plyr, tables

Suggests

License GPL-2

RoxygenNote 5.0.1

NeedsCompilation no

Author Anonymous Author [aut, cre]

Maintainer Anonymous Author <anonymous@author.edu>

R topics documented:

CrossScreening-package	2
bonferroni.fg	2
cross.screen	3
fallback.test	5
get.kappa	6
nhanes.fish	6
nhanes.fish.match	7
recycle.test	7
sen	8

9

Index

```
CrossScreening-package
```

Cross-screening for observational studies

Description

Cross-screening is a new method that uses both random halves of the sample to screen and test many hypotheses. It generally improves statistical power in observational studies when many hypotheses are tested simultaneously.

bonferroni.fg Bonferroni's correction with fixed Γ

Description

Bonferroni's correction with fixed Γ

Usage

bonferroni.fg(d, gamma = 1, mm = c(2, 2, 2), two.sided = TRUE)

Arguments

d	a matrix of treatment-minus-control differences.
gamma	sensitivity parameter (maximum odds different from a randomized experiment).
mm	test statistic, either a vector of length 3 or a matrix of three rows where each column corresponds to a U-statistic. Default is the (approximate) Wilcoxon's signed rank test.
two.sided	whether a two-sided test should be used. If FALSE, test the one-sided alternative that the center of d is positive.

Details

If mm is a matrix, this function computes a one-sided or two-sided p-value with each statistic (i.e. there is a p-value for every column of d and every column of \$mm\$), then does a Bonferroni correction over all the p-values.

Value

a vector of sensitivity values for each column of d

cross.screen

Description

Main functions that implements the cross-screening method in observational studies. cross.screen sorts the hypotheses by their sensitivity values and cross.screen.fg sorts by p-values at a fixed sensitivity Γ .

Usage

```
cross.screen(d1, d2, gamma = 1, mm = c(2, 2, 2), alpha.screen = 0.05,
gamma.screen = 0, two.sided = TRUE)
```

```
cross.screen.fg(d1, d2, gamma = 1, screen.method = c("threshold",
   "least_sensitive"), alpha.screen = 0.05, alpha.least.sensitive = 2,
   gamma.screen = gamma, mm = c(2, 2, 2), two.sided = TRUE)
```

Arguments

d1	screen/test sample (treatment-minus-control differences), can be a matrix (rows are observations, columns are hypotheses)	
d2	test/screen sample, can be a matrix	
gamma	sensitivity parameter (maximum odds different from a randomized experiment)	
mm	a vector of matrix. If matrix, adaptively choose statistic. NULL means Wilcoxon's signed rank statistic.	
alpha.screen	significance level used in screening.	
gamma.screen	screening threshold, default is 0, meaning no screening is used.	
two.sided	if TRUE, automatically select the sign to test; if FALSE, test the one-sided al- ternative that the center of d is positive.	
screen.method	either keep all hypotheses significant at gamma.screen (option "threshold") or keep the least sensitive hypotheses (option "least_sensitive").	
alpha.least.sensitive		
	the number of least sensitive hypotheses to keep	

Value

cross.screen returns a list

s1.kappa kappa values used to screen the hypotheses calculated using the first sample

sl.stat test statistics chosen using the first sample, if mm has more than 1 column

s1.side signs of alternative hypotheses chosen using the first sample

sl.order order of the hypotheses by sl.kappa if sl.kappa is above the threshold gamma.screen

p1 p-values computed using the first sample at sensitivity gamma

s2.kappa kappa values used to screen the hypotheses calculated using the second sample

s2.stat test statistics chosen using the second sample, if mm has more than 1 column

s2.side signs of alternative hypotheses chosen using the second sample

 $s2. order \ \ order \ of the hypotheses \ by \ s1. kappa \ if \ s1. kappa \ is above the threshold \ gamma. screen$

p2 p-values computed using the second sample at sensitivity gamma

p Bonferroni adjusted p-values at sensitivity gamma computed using p1 and p2 (they can be directly used to control FWER)

cross.screen.fg returns a list

s1.p p-values used to screen the hypotheses calculated using the first sample

sl.stat test statistics chosen using the first sample, if mm has more than 1 column

s1.side signs of alternative hypotheses chosen using the first sample

sl.order order of the hypotheses by s1.p if s1.p is below the threshold alpha.screen

p1 p-values computed using the first sample at sensitivity gamma

s2.p p-values used to screen the hypotheses calculated using the second sample

s2.stat test statistics chosen using the second sample, if mm has more than 1 column

s2.side signs of alternative hypotheses chosen using the second sample

s2.order order of the hypotheses by s2.p if s2.p is above the threshold alpha.screen

- p2 p-values computed using the second sample at sensitivity gamma
- **p** Bonferroni adjusted p-values at sensitivity gamma computed using p1 and p2 (they can be directly used to control FWER)

Functions

• cross.screen.fg: Cross-screening with fixed Γ

Examples

```
n <- 100
p <- 20
d <- matrix(rnorm(n * p), n, p)</pre>
d[, 1] <- d[, 1] + 2
d1 <- d[1:(n/2), ]
d2 <- d[(n/2+1):n, ]
cross.screen(d1, d2,
              gamma = 9,
              gamma.screen = 1.25)$p
## One can run the hidden function CrossScreening:::table5(no.sims = 1)
## to generate Table 5 in the paper.
## The following code generates Table 1 in the paper.
data(nhanes.fish)
data(nhanes.fish.match)
data <- nhanes.fish</pre>
match <- nhanes.fish.match</pre>
outcomes <- grep("^o\\.", names(data))</pre>
log2diff <- function(y1, y2) {</pre>
```

fallback.test

```
if (min(c(y1, y2)) == 0) {
        y1 <- y1 + 1
y2 <- y2 + 1
    }
    log2(y1) - log2(y2)
}
d <- sapply(outcomes, function(j) log2diff(data[match$treated, j], data[match$control, j]))</pre>
set.seed(11)
split <- sample(1:nrow(d), nrow(d) / 2, replace = FALSE)</pre>
d1 <- d[split, ]
d2 <- d[-split, ]
mm <- matrix(c(2, 2, 2, 8, 5, 8), ncol = 2)</pre>
data.frame(outcome = names(data)[outcomes],
           p.value =
                cross.screen.fg(d1, d2,
                                 gamma = 9,
                                 screen.method = "least_sensitive",
                                 mm = mm)$p)
```

fallback.test

Fallback procedure for multiple testing

Description

Fallback procedure for multiple testing

Usage

fallback.test(p, alpha = 0.05, spread = 1)

Arguments

р	a vector of p-values
alpha	significance level
spread	the way to spread alpha, either a vector of the same length as p or a single number to indicate equal spread in the first spread hypotheses.

Value

the rejected hypotheses

References

Brian L. Wiens. A fixed sequence Bonferroni procedure for testing multiple endpoints. Pharmaceutical Statistics, 2(3), 211–215, 2003.

get.kappa

Description

Compute sensitivity value

Usage

get.kappa(d, alpha = 0.05, mm = c(2, 2, 2))

Arguments

d	a vector of treatment-minus-control differences
alpha	significance level
mm	test statistic, either a vector of length 3 or a matrix of three rows where each column corresponds to a U-statistic. Default is the (approximate) Wilcoxon's signed rank test.

Details

The alternative direction is the the center of d is greater than 0.

Value

sensitivity value, i.e. the kappa value such that the p-value becomes just insignificant. If mm is a matrix, then return a vector of sensitivity values corresponding to each column of mm.

nhanes.fish

Health effects of fish

Description

Data from NHANES (2013-2014) with 1107 observations and 87 variables. Variables whose name start with "o." are lab measurements (such as blood mercury) that can be used as outcomes. The demographics and background variables include gender, age, income, indicator for missing income, race, education, indicator for smoked ever, number of cigararttes smoked in the last month. Fish intakes in the last month (in servings) are summed up in the "fish" variable, which is used to create the binary indicator "fish.level".

Usage

data(nhanes.fish)

Format

A data.frame.

nhanes.fish.match Pair matching result

Description

Each row is a matched pair, the first/second entry is the id of low/high fish intake in the nhanes.fish data frame.

Usage

```
data(nhanes.fish.match)
```

Format

A data.frame.

recycle.test Recycling procedure for multiple testing

Description

Recycling procedure for multiple testing

Usage

recycle.test(p, alpha = 0.05)

Arguments

р	a vector of p-values
alpha	significance level

Details

WARNING: only supports recycle the first two tests.

Value

rejected hypotheses

Description

Sensivity analysis with signed score test

Usage

```
sen(y, mm = NULL, gamma = 1, tail = c("upper", "lower"))
```

Arguments

У	a vector of treatment-minus-control differences
mm	a vector (m, munder, mover) that indicates the U-statistic. NULL means Wilcoxon's signed rank test.
gamma	sensitivity parameter >= 1.
tail	report p-value corresponds to the maximum ("upper") or minimum ("lower") bound

Value

A list

pval p-value

pval2 two sided p-value

T test statistic

E Mean of the test statistic under sensivity gamma

V Variance of the test statistic under sensitivity gamma

devc Effect size of T compared to E and V

sen

Index

*Topic datasets
 nhanes.fish,6
 nhanes.fish.match,7

bonferroni.fg, 2

cross.screen, 3
CrossScreening-package, 2

fallback.test,5

get.kappa,<mark>6</mark>

nhanes.fish, 6
nhanes.fish.match,7

recycle.test,7

sen, <mark>8</mark>