Commit description

❚❚ Pause

Allow columns to be rearranged in file system browser

Code changes

Below you find the code changes to review. The old version of the code is on the left, the new version is on the right.

To add a review remark, click on the respective line number. To delete it, click on it again and delete the remark's text. If a defect spans multiple lines, just mark one of those lines. If similar defects appear multiple times, please mark every occurrence. If you suspect something could be a defect but are not 100% sure, it's better to add a review remark.

At several of the change parts, you can show the whole changed method by clicking on "(Show more context)".

org/experiment/editor/browser/VFSDirectoryEntryTable.java, constructor

org/experiment/editor/browser/VFSDirectoryEntryTable.java, constructor
(Show more context)

```
66        setDefaultRenderer(Entry.class,
67            renderer = new FileCellRenderer());
68
69        header = getTableHeader();
70        header.setReorderingAllowed(false);
71        addMouseListener(new MainMouseHandler());
72        header.addMouseListener(new MouseHandler());
73        header.setDefaultRenderer(new HeaderRenderer(
74            (DefaultTableCellRenderer)header.getDefaultRenderer()));
```

```
66        setDefaultRenderer(Entry.class,
67            renderer = new FileCellRenderer());
68
69        header = getTableHeader();
70        header.setReorderingAllowed(true);
71        addMouseListener(new MainMouseHandler());
72        header.addMouseListener(new MouseHandler());
73        header.setDefaultRenderer(new HeaderRenderer(
74            (DefaultTableCellRenderer)header.getDefaultRenderer()));
```

org/experiment/editor/browser/VFSDirectoryEntryTableModel.java

org/experiment/editor/browser/VFSDirectoryEntryTableModel.java, columnMoved()

```
275
```

```
275    protected void columnMoved(int from, int to) {
276        if (from == to)
277            return;
278        if (from < 1 || from >= getColumnCount())
279            return;
280        if (to < 1 || to >= getColumnCount())
281            return;
282        ExtendedAttribute ea = extAttrs.remove(from - 1);
283        extAttrs.add(to - 1, ea);
284    }
285
```

org/experiment/editor/browser/VFSDirectoryEntryTable.java

org/experiment/editor/browser/VFSDirectoryEntryTable.java (Show more context)

```
574    class ColumnHandler implements TableColumnModelListener        574    class ColumnHandler implements TableColumnMode
575    {                                                              575    {
576        public void columnAdded(TableColumnModelEvent e) {}        576        public void columnAdded(TableColumnModelEvent e) {}
577        public void columnRemoved(TableColumnModelEvent e) {}      577        public void columnRemoved(TableColumnModelEvent e) {}
578        public void columnMoved(TableColumnModelEvent e) {}        578        public void columnMoved(TableColumnModelEvent e) {
579        public void columnSelectionChanged(ListSelectionEvent e) {} 579            ((VFSDirectoryEntryTableModel)getModel()).columnMoved(
580                                                                    580                    e.getToIndex(), e.getFromIndex());
581        public void columnMarginChanged(ChangeEvent e)             581        }
582        {                                                          582        public void columnSelectionChanged(ListSelectionEvent e) {}
                                                                      583
                                                                      584        public void columnMarginChanged(ChangeEvent e)
                                                                      585        {
```

End review ▶